








- NL** Accumulerende draagrol met een stalen, dubbelrijige kettingkop, voorzien van twee groefkogellagers. Door toepassing van een wrijvingskoppeling is deze uitvoering geschikt voor een accumulerende rollenbaan t.b.v. het transporteren van zware producten met een harde, vlakke onderkant.
- D** Stauangetriebene Tragrolle mit Stahl-Mehrfachkettenrad, ausgestattet mit zwei Rillenkugellagern. Durch Reibungskupplung ist diese Tragerolle geeignet für Akkumulations-Rollenbahn zum Transport von schweren Produkten mit festem, flachem Boden.
- GB** Accumulating conveyor roller with a double steel sprocket, fitted with two grooved ball bearings. Because it makes use of a friction coupling, this version is suitable for an accumulating roller conveyor for the transportation of heavy products with hard and flat undersides.

**SPECIFICATIONS:**

							<b>OPTIONS:</b>		
5/8x3/8* Z=15	0,05 - 0,07	STEEL C45	6204-6005	200 KG		STEEL - ORANGE		ZINKPLATED	SS

Spindel Steel/SS							
Ø 20	M 10 x 15 M 12 x 20		sw 15 x 10 sw 14 x 10		Ø 20 x 15	M 20 x 25	met BD M 16 x 20

Tube	Steel Zinkplated	Stainless steel	PVC 5005	PVC 7011
Ø 63.5 x 2.9	x			
Ø 80 x 2.0	x	x		
Ø 82.5 x 3.2	x			
Ø 88.9 x 3.2	x	x		