



- NL** Draagrol met kunststof lagerpotten, voorzien van een polyamide glijlager. Geschikt om lichte producten op een bandtransporteur of aangedreven rollenbaan in een zeer vochtige, agressieve omgeving te transporteren. Speciaal voor toepassingen in de voedingsindustrie.
- D** Tragrolle mit Kunststoff-Lagerböden und Polyamid-Gleitlagern. Geeignet um leichte Produkte auf einem Bandförderer oder einer angetriebenen Rollenbahn zu transportieren. Einsatz: in sehr feuchten und aggressiven Räumen, insbesondere in der Nahrungsmittelindustrie.
- GB** Conveyor roller with plastic roller bearing, fitted with polyamide sleeve bearing. Suitable for transporting lightweight products on a belt conveyor or powered roller conveyor in a very humid, aggressive environment. Especially for applications within the food industry.

SPECIFICATIONS:



Spindel Steel/SS							Tube	Steel Zinkplated	Stainless steel	PVC 5005	PVC 7011
Ø 6				Ø 6 x 10	M 6 x 15		Ø 30 x 1.5	x	x		
Ø 8	M 5 x 12		sw 6 x 10	Ø 8 x 10	M 8 x 15	met BD M 6 x 15	Ø 30 x 1.8			x	x
Ø 10	M 6 x 12		sw 8 x 10	Ø 10 x 10	M 10 x 15	met BD M 8 x 15	Ø 30 x 2.0	x	x		
Ø 12	M 6 x 12 M 8 x 15		sw 10 x 10	Ø 12 x 10	M 12 x 15	met BD M 10 x 15	Ø 40 x 1.5	x	x		
							Ø 40 x 2.3			x	x